

## **5-7: M&G-1 MINING AND GRAZING ZONE**

### **E. WIDTH REQUIREMENTS**

The minimum width of a zoning lot within the M&G-1 Zone shall be as follows:

1. For each one-family dwelling, family day-care center, foster care home, residential facility for handicapped persons, or residential facility for elderly persons, the minimum width of the lot at any point between the frontage and the structure shall be three hundred thirty (330) feet.

However, without regard to the width requirement stated above, if the property is included in a recorded large-scale development plat, the required width shall be the width of the undivided lot or dwelling site as depicted on such plat.

2. For each residential treatment center the minimum width of the lot between the frontage and the structure shall be three hundred thirty (330) feet.

3. For each church or other structure for public worship, or church with parsonage, the minimum width of the lot at any point between the frontage and the structure shall be three hundred thirty (330) feet.

4. For each preschool, or primary or secondary school, the minimum width of the lot at any point between the frontage and the structure shall be three hundred thirty (330) feet.

5. For each public park containing approved concessions or landscape park containing approved recreational facilities, the minimum width of the lot along the road frontage shall be three hundred thirty (330) feet.

6. For each governmental building and facility permitted under zoning section 5-7-B-37, the minimum width of the lot along the road frontage shall be three hundred thirty (330) feet.

7. For other permitted structures and uses, there shall be no minimum width requirements except as may be required under other provisions of this ordinance.